FLORENCE-Z60

~60° wide beam. Ideal for retail and industrial lighting. Can be used for general office lighting with shade.



SPECIFICATION:

Dimensions	286.0 x 61.0
Height	8.5 mm
Fastening	screw
ROHS compliant	yes


MATERIALS:

Component	Type	Material	Colour	Finish	Length (mm)
FLORENCE-Z60	Linear lens	PMMA	clear		

ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
F14112_FLORENCE-Z60	72	18	6	7.3
» Box size: 398 x 298 x 140 mm				

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.




See also our general installation guide: www.ledil.com/installation_guide

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

CREE LEDs

LED	XH-B/G
FWHM / FWTM	43.0° / 111.0°
Efficiency	87 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

inventronics

LED	PL-BAR-G3 1100 280x55
FWHM / FWTM	57.0° / 109.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	







Light distribution files

LUMILEDS

LED	LUXEON 3030 2D (Round LES)
FWHM / FWTM	57.0° / 107.0°
Efficiency	88 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMILEDS

LED	LUXEON 3535 2D
FWHM / FWTM	57.0° / 108.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

LUMILEDS

LED	LUXEON 3535L HE
FWHM / FWTM	58.0° / 110.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	







Light distribution files

LUMILEDS

LED	LUXEON XR-3535L (L202 - xxxx033C30001)
FWHM / FWTM	59.0° / 108.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

LUMINUS

LED	MP-2016
FWHM / FWTM	58.0° / 105.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

NICHIA

LED	NF2x757D
FWHM / FWTM	58.0° / 107.0°
Efficiency	92 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

NICHIA

LED	NFSW757H
FWHM / FWTM	58.0° / 110.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED	Duris E5
FWHM / FWTM	59.0° / 109.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

OSRAM
Opto Semiconductors

LED	Duris S2
FWHM / FWTM	55.0° / 111.0°
Efficiency	90 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

OSRAM
Opto Semiconductors

LED	Duris S5 (Single chip)
FWHM / FWTM	58.0° / 107.0°
Efficiency	89 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

OSRAM
Opto Semiconductors

LED	OSLON Square CSSRM2/CSSRM3
FWHM / FWTM	56.0° / 111.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	







Light distribution files

PHILIPS

LED	Fortimo LED Line VO 1ft MF 3R HV5
FWHM / FWTM	55.0° / 107.0°
Efficiency	95 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

PHILIPS

LED	Fortimo LED Line 1ft 650lm 3R HV4 & LV4
FWHM / FWTM	58.0° / 108.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

PHILIPS

LED	Fortimo LED Line 1ft HF 3R HV5
FWHM / FWTM	56.0° / 107.0°
Efficiency	95 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

PHILIPS

LED	Fortimo LED Line 1ft LF 3R HV5 & LV5
FWHM / FWTM	57.0° / 107.0°
Efficiency	95 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

PHILIPS

LED	Fortimo LED Line 1ft MF 3R HV5 & LV5
FWHM / FWTM	56.0° / 108.0°
Efficiency	95 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LM231 A/B
FWHM / FWTM	56.0° / 107.0°
Efficiency	89 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

SAMSUNG

LED	LM362A
FWHM / FWTM	59.0° / 107.0°
Efficiency	85 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

SAMSUNG

LED	LM561B
FWHM / FWTM	59.0° / 108.0°
Efficiency	86 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED	LM561B Plus
FWHM / FWTM	59.0° / 109.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

SAMSUNG

LED	LM561C
FWHM / FWTM	59.0° / 110.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	







Light distribution files

SAMSUNG

LED	LT-R286A
FWHM / FWTM	58.0° / 110.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

SEOUL SEMICONDUCTOR

LED	SEOUL 3030
FWHM / FWTM	56.0° / 108.0°
Efficiency	92 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

SEOUL SEMICONDUCTOR

LED	SEOUL 5630C
FWHM / FWTM	57.0° / 109.0°
Efficiency	92 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

SEOUL SEMICONDUCTOR

LED	SEOUL DC 3030
FWHM / FWTM	59.0 + 55.0° / 106.0 + 108.0°
Efficiency	93 %
Peak intensity	0.9 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	





Light distribution files


LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (MEASURED):

TRIDONIC

LED	LLE G2 55x280mm 2000lm
FWHM / FWTM	58.0° / 111.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	






Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

CREE LEDs


LED	J Series 5050 Round LES
FWHM / FWTM	68.0° / 101.0°
Efficiency	93 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

CREE LEDs


LED	J Series 5050C 6V E Class
FWHM / FWTM	66.0° / 102.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

LUMILEDS

LED	LUXEON 5050 Round LES
FWHM / FWTM	65.0° / 101.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA


LED	NF2x757G
FWHM / FWTM	62.0° / 94.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA


LED	NFMW48xA
FWHM / FWTM	64.0° / 105.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

NICHIA

LED	NFSx757G
FWHM / FWTM	63.0 + 68.0° / 110.0 + 100.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

NICHIA


LED	NVSxE21A
FWHM / FWTM	70.0° / 94.0°
Efficiency	87 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors


LED	Duris E 2835
FWHM / FWTM	50.0° / 99.0°
Efficiency	92 %
Peak intensity	1 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors

LED	Duris E 2835
FWHM / FWTM	68.0 + 57.0° / 100.0 + 97.0°
Efficiency	92 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED	Duris S8
FWHM / FWTM	70.0° / 106.0°
Efficiency	94 %
Peak intensity	0.7 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

OSRAM
Opto Semiconductors


LED	OSCONIQ C 2424
FWHM / FWTM	66.0° / 96.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG

LED	LH351D
FWHM / FWTM	59.0° / 106.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED	LM28xB Series
FWHM / FWTM	66.0° / 97.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG


LED	LM301B
FWHM / FWTM	68.0° / 106.0°
Efficiency	93 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG

LED	LM301B
FWHM / FWTM	66.0° / 98.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED	LM302Z plus
FWHM / FWTM	68.0° / 105.0°
Efficiency	93 %
Peak intensity	0.7 cd/lm
LEDs/each optic	2
Light colour/type	White
Required components:	



Light distribution files

SAMSUNG


LED	LM302Z plus
FWHM / FWTM	66.0° / 98.0°
Efficiency	94 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SEOUL SEMICONDUCTOR

LED	SEOUL 5630D
FWHM / FWTM	65.0° / 95.0°
Efficiency	91 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	




Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

OPTICAL RESULTS (SIMULATED):

SEOUL SEMICONDUCTOR

LED	SEOUL DC 3030C
FWHM / FWTM	66.0° / 98.0°
Efficiency	95 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	



Light distribution files

SEOUL SEMICONDUCTOR

LED	Z8Y22
FWHM / FWTM	62.0° / 100.0°
Efficiency	93 %
Peak intensity	0.8 cd/lm
LEDs/each optic	1
Light colour/type	White
Required components:	

Light distribution files

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy
Joensuunkatu 7
FI-24240 SALO
Finland

LEDiL Inc.
228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.
405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support
www.ledil.com/
where_to_buy

Shipping locations
Poznan, Poland
Hong Kong, China

Distribution Partners
www.ledil.com/
where_to_buy

LEDiL is a registered trademark of LEDiL Oy in the European Union, USA, and certain other countries.